



KANOMAX
The Ultimate Measurements

Digital Dust Monitor

MODEL 3444

Compact & Lightweight w/ built-in pump



New Dust Monitor with Suction Pump

- Compact & Lightweight w/ built-in pump
- Tubing, classification system, etc functions available
- Simple calibration available w/ instructions
- Extremely short time calibration
- Real-time monitoring available w/ software
- Color screen
- Languages: English, Japanese

Protector can be attached to main unit



SPECIFICATIONS

Product Name	Digital Dust Monitor	
Model	3444	
Measurement Range	0.001 to 10.000mg/m ³ (1 CPM=0.001 mg/m ³ @standard particle)	
Accuracy	± (10% of the reading value +1) count	
Linearity	±5% of the reading value	
Meas. Modes	① Standard mode (6, 10, 30sec / 1, 2, 3, 5, 10min) ② Free mode (1 to 59sec or 1 to 99min) ③ Manual mode (manual operation to start & end the measurement) ④ TWA mode (measurement interval time & alarm can be set) ⑤ Calculation mode (meas. start time, meas. period of time, meas. times can be set, based on repeat meas.) (* Meas. data is automatically saved on internal storage) ⑥ User calibration (Background, sensitivity adjustment) ⑦ Cleaning	
Optical Source	Semiconductor Laser Diode	
Detector	Photodiode	
Meas. Method	Light Scattering Method	
Display	Color LCD display	
Output	Analog output (*output range can be selectable)	0 to 1,000CPM (0 to 1V) 0 to 10,000CPM (0 to 1V) 0 to 1,000CPM (0 to 1V, 1,000 to 10,000CPM, 0.1 to 1V (AUTO))
	Pulse output (*photocoupler output)	
	Alarm output (*photocoupler output)	
Communication	USB port (reading saved data, parameter setting, remote measurement)	
K value	Available to set (*setting range: 0.1 to 9.9, 0.1 step) (*Factor of Mass Concentration Conversion Coefficient)	
Data Storage	Max. 100,000 data (*saved data can be read on display)	
Power	AA batteries (*6 pcs)	
	AC adapter (AC100 to 240V) (*option)	
Operational Environment	Temperature: 5 to 40°C, Humidity: 95% or less (*no condensation)	
Storage Environment	Temperature: 0 to 45°C, Humidity: 95% or less (*no condensation)	
Dimension	162 x 60 x 109 mm	
Weight	Approx. 1.3kg (*including six AA batteries)	
Standard Accessories	Shoulder strap, AA battery (6 pcs), LCD protective sheet, USB cable, PC software, instruction manual	
Optional Accessories	Analog output cable, communication input&output cable, USB cable for communication, Cyclone connection adapter, Tripod fixing L-shape bracket, Main unit cover, Protector, Pump filter, Purge filter, AC adapter, Tube connection inlet adapter	



KANOMAX
The Ultimate Measurements

KANOMAX USA, INC.

219 US Highway 206, Andover NJ 07821
 TEL : +1-973-786-6386
 E-mail : sales@kanomax-usa.com
 URL : https://kanomax-usa.com

BCT ENTERPRISE CO., LTD.

40/24 Moo 5, Lumlukka, Pathumthani
 12150
 Tel. 081 682 5558
 www.bct-enterprise.com
 Email: info@bct-enterprise.com